

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

WO 97/32423

(51) International Patent Classification ⁶ : H04M 1/02		(11) International Publication Number: A1	(11) International Publication Number: WO 97/32423 (43) International Publication Date: 4 September 1997 (04.09.97)
(21) International Application Number: PCT/EP97/00909 (22) International Filing Date: 24 February 1997 (24.02.97)		(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(30) Priority Data: 96102988.1 28 February 1996 (28.02.96) EP (34) Countries for which the regional or international application was filed: AT et al.		Published With international search report.	
(71) Applicant (for all designated States except US): NOKIA MOBILE PHONES LIMITED [FI/FI]; P.O. Box 86, FIN-24101 Salo (FI).			
(72) Inventors; and (75) Inventors/Applicants (for US only): FUHRMANN, Thomas [DE/DE]; Buldergeist 48, D-48249 Dülmen (DE), WILKE, Annett [DE/DE]; Castropor Strasse 205, D-44791 Bochum (DE), UMBACH, Dirk [DE/DE]; Rheinstrasse 48, D-45525 Hattingen (DE).			
(74) Agents: FRAIN, Timothy, John et al.; Nokia Mobile Phones, Patent Dept., St. Georges Court, St. Georges Road, Camberley, Surrey GU15 3QZ (GB).			

(54) Title: ELECTRONIC DEVICE WITH HOUSING SUPPLEMENT



(57) Abstract

The invention relates to an electronic device having a housing (1) which has a housing wall (5) with openings (7) for control elements (8) and/or display elements (9, 10). Attachment means (11) for detachably connecting to the housing (1) an external wall element (14) which at least partially covers the housing wall (5) being present on the housing (1), the external wall element (14) having openings (7') which are aligned with the openings (7) in the housing wall (5). As a result, by using different external wall elements (14) the external appearance of the electronic device can be easily modified.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	L1	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TC	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

PCT/EP97/00909

WO 97/32423

ELECTRONIC DEVICE WITH HOUSING SUPPLEMENT

The invention relates to an electronic device having a housing which has a housing wall with openings for control and/or display elements.

An electronic device of this kind may be for example a telephone, a cordless phone or mobile phone, a pocket calculator, a television set, a radio receiver or for example another electronic domestic appliance which, as a rule, is used by private individuals. If, for personal reasons or because of predetermined requirements, the external appearance of such an electronic device, for example the shape of the housing or its colour, is to be modified, as a rule this must be carried out by a specialist since during such an operation the electronic components present in the housing of the electronic device are usually exposed. Modification of the appearance of the housing of the electronic device is thus laborious, time-consuming and expensive and, moreover, can as a rule only rarely be carried out by private individuals.

In accordance with the invention there is provided an electronic device having a housing which has a housing wall with openings for control elements and/or display elements, characterized by attachment means for detachably connecting to the housing an external wall element which at least partially covers the housing wall, the external wall element having openings which are aligned with the openings in the housing wall. Advantageous refinements of the invention can be found in the subclaims.

An electronic device in accordance with the invention allows the external appearance of the housing to be modified rapidly and easily even by non-professionals.

PCT/EP97/00909

WO 97/32423

With the electronic device according to the invention, a user thus has the possibility of modifying the appearance or design of the housing in an extremely short time and without any difficulty by selecting and fitting on an appropriate external wall element. The user can thus more or less change the housing according to his wishes if external elements with different shapes and colours are available to him for this purpose. Even external wall elements made of different materials are possible.

When the housing wall provided with openings is covered by the external wall element, the openings provided in the housing wall and in the external wall element are aligned with one another so that for example the push-button keys which project through the openings can continue to be used even after the external wall element is fitted on to the housing wall or display elements which are inserted into the openings can continue to be read. This also applies to microphones or loudspeakers inserted into opening, for example in the case of cordless telephones.

With the electronic device according to the invention, the electronics provided in the device are always protected against access by the customer when the external appearance of the housing is modified. Therefore, if one external wall element is to be replaced by another in order to give the electronic device a new design, there is no risk of the electronics present in the housing being damaged when the external wall elements are interchanged or of the user being subjected to danger by the electronics present inside the housing. In this respect, the external wall elements could even be interchanged when an electronic device is operating.

According to an advantageous refinement of the invention, the external wall element can engage, at least partially, over further housing walls of the housing so that the design of the housing can be modified to an even greater extent or adapted to the wishes of the user to an even greater degree.

WO 97/32423

PCT/EP97/00909

At the same time, the profile of the external wall element can follow the profile of the housing walls of the housing if emphasis is being placed not so much on the modification of the shape of the housing but rather on changing the colour or the type of material of the housing. However, the external wall elements can of course have different shapes which can also deviate from one another to a greater degree provided it is ensured that after the respective external wall elements have been connected to the housing the respective openings in the fitted-on external wall element and in the housing wall in question are aligned with one another.

According to a very advantageous development of the invention, the external wall element can be of, for example, shell-shaped design so that it can be fitted for example with one edge on to a base which projects outwards beyond the side walls of the housing.

Any desired attachment means can be used to attach the external wall element to the housing of the electronic device, but attachment means with press-on/catch closure can preferably be used. They ensure a secure connection between the external wall element and the housing and, moreover, can be easily used without a special tool being required for them.

The invention is explained in detail below with reference to the drawing, in which:

Figure 1 shows a cordless telephone or mobile phone with external wall element removed;

Figure 2 shows the cordless or mobile phone according to Figure 1 with the external wall element fitted on;

WO 97/32423

PCT/EP97/00909

Figure 3 shows the external wall element from the underside; and

Figure 4 shows a section through the wall of the external wall element.

The invention is explained below with reference to a cordless telephone or mobile phone which serves as an example of an electronic device. However, the invention can also be used in other electronic devices, for example in wire-connected telephones, in pocket calculators, in television sets, in radio receivers, in CD players, in cassette recorders etc.

In accordance with Figure 1, a cordless telephone or mobile phone according to the invention has a housing 1 with which a plate-shaped base element 2 and a shell-shaped housing element 3 are associated. The plate-shaped based element 2 and the shell-shaped housing element 3 are connected to one another using screws (not illustrated) which project through openings 4 in the shell-shaped housing element 3 and are screwed into sockets (not illustrated) which are fixedly connected to the inside of the plate-shaped base element 2. Inside the housing 1 there is a carrier plate, attached in a suitable way, for electronic components etc.

The shell-shaped housing element 3 has a housing wall 5 which is located essentially parallel with the plate-shaped base element 2 and at a distance therefrom and is integrally connected to side walls 6 which are supported with their free or lower edge on the plate-shaped base element 2. In this arrangement, the plate-shaped base element 2 projects outwards beyond the side walls 6 by constant distance in its edge region so that a profile with an identical contour is obtained.

In the housing wall 5 there is a plurality of through-openings 7 for electronic components which are mounted on the carrier plate, already mentioned, inside the housing 1, and partially project through the through-openings 7. The through-openings 7 can be provided for example for push-button keys 8, for a

WO 97/32423

PCT/EP97/00909

display device 9 or for a loudspeaker device/microphone device 10. A corresponding through-opening 7 may also be present in the upper side wall 6 for an aerial.

On the side walls 6, extending in the longitudinal direction of the housing 1, of the shell-shaped housing element 3 there are also in each case two attachment means 11 which are designed as press-on/catch closures at a distance from one another. They are located in each case at the front and rear ends of the telephone. The attachment means 11 have a catch projection 12 which is prestressed outwards in a sprung fashion and can be pressed inwards into the housing 1 counter to the outwardly acting spring force by means of an externally accessible activation element 13. These attachment means serve to attach to the housing 1 an external wall element 14 which is fitted on to the shell-shaped housing element 3 and is also of shell-shaped design.

The shell-shaped external wall element 14 which is illustrated in Figures 1 and 3 has approximately the same contour as the shell-shaped housing element 3 but is designed in such a way that it can receive the shell-shaped housing element 3 in it. If the external wall element 14, which is designed as a thin-walled shell, is fitted on to the shell-shaped housing element 3, the shell-shaped external wall element 14 is supported with the free or downwardly pointing edge of its side walls on that part of the plate-shaped base element 2 which projects outwards beyond the shell-shaped housing element 3. Here, the wall thickness of the side walls of the shell-shaped external wall element 14 corresponds to the distance by which the edge of the plate-shaped base element 2 projects outwards beyond the side walls 6, 6' of the shell-shaped housing element 3. As a result, no step remains in the connection area between the shell-shaped external wall element 14 and the plate-shaped base element 2. The height of the side walls of the shell-shaped external wall element 14 can be selected here such that the main face of the external wall element 14 comes to rest at a short distance from the housing wall 5 and as a result does not exert any pressure on the latter.

PCT/EP97/00909

WO 97/32423

Likewise, openings 7' which are aligned with the openings 7 in the housing wall 5 of the shell-shaped housing element 3 are provided in the main face of the external wall element 14. Therefore, it is possible to continue to operate the telephone even when the external wall element 14 is fitted on to the shell-shaped housing element 3. At the same time, the push-button keys 8 can be of such a height that they also project outwards beyond the external wall element 14. Openings which are present in the external wall element 14 for the display device 9 and the loudspeaker device/microphone device 10 can be covered, for example by means of a transparent element 15 or a grill 16.

Figure 2 shows the cordless telephone or mobile phone in a state in which the shell-shaped external wall element 14 is fitted on to the shell-shaped housing element 3 and is detachably connected to the housing 1. On the internal faces of the long side walls of the external wall element 14 there are notches 12', one of which is seen in section in Figure 4, for the catch projections 12 of the attachment means 11 so that the catch projections 12 engage in the notches 12' as a result of the outwardly pressing spring force, and thus hold the external wall element on the housing 1. In this state, the activation elements 13 are also pushed outwards but only to such an extent that they do not project beyond the side edge of the plate-shaped base element 2 or of the external wall element 14. The activation elements 13 can extend here in a groove 17 in the upper face of the plate-shaped base element 2. If the activation elements 13 are pressed inwards, that is to say inwards along the groove 17, for example using a pointed object, they move the catch projections 12 correspondingly inwards along with them so that the said catch projections 12 disengage from the notches 12' on the inside of the side walls 6 of the external wall element 14. The external wall element 14 can then be removed from the housing 1.

The external wall element 14 is fitted on to the housing 1 by simply pressing it on. The catch projections 12 then engage automatically in the notches 12'.

WO 97/32423

PCT/EP97/00909

The present invention includes any novel feature or combination of features disclosed herein either explicitly or any generalisation thereof irrespective of whether or not it relates to the claimed invention or mitigates any or all of the problems addressed.

In view of the foregoing description it will be evident to a person skilled in the art that various modifications may be made within the scope of the invention.

PCT/EP97/00909

WO 97/32423

CLAIMS

1. Electronic device having a housing (1) which has a housing wall (5) with openings (7) for control elements (8) and/or display elements (9,10), characterized by attachment means (11) for detachably connecting to the housing (1) an external wall element (14) which at least partially covers the housing wall (5), the external wall element (14) having openings (7') which are aligned with the openings (7) in the housing wall (5).
2. Electronic device according to Claim 1, characterized in that the external wall element (14) engages, at least partially, over further housing walls (6, 6') of the housing (1).
3. Electronic device according to Claim 1 or 2, characterized in that the profile of the external wall element (14) follows the profile of the housing walls (5, 6, 6') of the housing (1).
4. Electronic device according to Claim 1, 2 or 3, characterized in that the external wall element (14) is of shell-shaped design.
5. Electronic device according to Claim 2, 3 or 4, characterized in that the housing (1) has a base (2) which projects beyond side walls (6, 6') of the housing (1) and on to which the external wall element (14) can be fitted with its edge.
6. Electronic device according to one of Claims 1 to 5, characterized in that the attachment means (11) have at least one press-on/catch closure (12, 13).
7. Electronic device according to one of Claims 1 to 6, characterized in that it is designed as a telephone.

WO 97/32423


PCT/EP97/00909

8. Electronic device according to Claim 7, characterized in that the telephone is a cordless telephone or a mobile phone.

WO 97/32423

PCT/EP97/00909

1/3




WO 97/32423

PCT/EP97/00909

2/3

Fig.2.



WO 97/32423

PCT/EP97/00909

3/3

Fig.3.





Fig.4.



INTERNATIONAL SEARCH REPORT

Int'l. Appl. No
PCT/EP 97/00909

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04M1/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 146 615 A (HODSDON ET AL) 8 September 1992 see column 4, line 60 - column 6, line 65; figures 1-8 ---	1,7,8
X	US 4 292 481 A (BARNES ET AL) 29 September 1981 see column 2, line 40 - column 6, line 3; figures 1-4 ---	1,7
X	US 4 433 216 A (ISAACS) 21 February 1984 see column 1, line 60 - column 3, line 17; figures 1-8 ---	1,7
A	US 5 140 632 A (ANTEN) 18 August 1992 see column 3, line 4 - column 5, line 2; figures 1-5 ---	1-3,7,8
		-/-

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

* Special categories of cited documents :

- 'A' document defining the general state of the art which is not considered to be of particular relevance
- 'E' earlier document but published on or after the international filing date
- 'L' document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- 'O' document referring to an oral disclosure, use, exhibition or other means
- 'P' document published prior to the international filing date but later than the priority date claimed

'T' later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

'X' document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

'Y' document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

'A' document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

16 May 1997

18.05.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax (+31-70) 340-3016

Authorized officer

Delangue, P

INTERNATIONAL SEARCH REPORT

Int'l. Appl. No.
PCT/EP 97/00909

C(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		Relevant to claim No.
Category	Citation of document with indication, where appropriate, of the relevant passages	
A	US 5 134 654 A (MCGOUGH) 28 July 1992 see column 2, line 15 - line 66; figures 1-3 ---	1-3,7
P,X	GB 2 293 517 A (MOTOROLA INC) 27 March 1996 see page 4, line 4 - page 8, line 34; figures 1,2 -----	1,7,8

1

INTERNATIONAL SEARCH REPORT

Information on parent family members

International Application No
PCT/EP 97/00989

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5146615 A	08-09-92	CA 2016010 A	07-02-91
US 4292481 A	29-09-81	NONE	
US 4433216 A	21-02-84	NONE	
US 5140632 A	18-08-92	NONE	
US 5134654 A	28-07-92	NONE	
GB 2293517 A	27-03-96	AU 3051895 A BR 9504702 A CA 2157625 A CN 1123999 A FR 2724798 A JP 8097888 A ZA 9507946 A	04-04-96 08-10-96 21-03-96 05-06-96 22-03-96 12-04-96 18-04-96